

## Job Safety Analysis

Safety Information for The University of North Carolina at Chapel Hill

## JOB SAFETY ANALYSIS TOPIC:

## Sanitizing IVC Half Racks from the Rack Washer



Title	Work Task	Hazards	Controls
Preplan the work	Gather proper tools and equipment (1 clean and 1 dirty half rack)  Gather PPE: Personal Protective Equipment (PPE) consisting of yellow isolation gown, gloves, steel toe shoes	Improper tools Improper/No Equipment Inspection Improper PPE inspection/selection	2 Half Racks are used to create stability and to prevent the half rack from tilting or falling during wash cycle (Do NOT use other objects to support the half rack).
Before the job	Don necessary PPE Inspect Rack Washer Door, Washer area and the IVC half rack. Make sure Rack Washer is powered on and ready for service.	Improper Donning	Improperly donning or not donning PPE can lead to an unnecessary exposure.  Familiarize yourself with the location and proper use of all controls and safety devices.  Make sure the rack washer is free of obstructions such as: racks, equipment, cages etc.

Begin the sanitizing	1. Open the rack washer door.		Ergonomic	Check throughout the cycle to make sure	
operation	1		8	the racks have not moved or adjusted	
	2. Push the IVC Half Rack inside the		Fall Hazards	during the cleaning cycle.	
The state of the s	Rack Washer toward the left side		1 WII 11W2WI W5	awang uno cromming of cro	
	where cage side of rack is facing the		Foot Hazard		
	wall and back side of rack is facing		1001111111111		
Ekil E CLL	the middle of the rack washer.		Hand injury		
	the imagic of the fack washer.		Trana injury		
	3. Push the second IVC Half Rack				
	inside the Rack Washer toward the				
	right side where cage side of rack is				
	facing the wall and back side of rack				
	is facing the middle of the rack				
	washer.				
	washer.				
	4. Start Cycle.				
Completing the sanitizing	Open the washer door.		Ergonomic	Clean up any excess water or spills	
operation				immediately to prevent falling.	
	Remove the two racks.		Fall Hazards		
				Check the IVC rack for any damage	
	Doff PPE and dispose of it in		Foot Hazard	after removing from the washer.	
	proper locations			(Report any damages to the	
			Hand injury	supervisor and remove the rack from	
				service use)	
Training	Employees must have hands on train	ing in	Supervisor is to fill ou	at the turn in the form to UNC-CH	
				ing Form' and Environment, Health and Safety	
			for documentation of p	•	
				-	
	Neah Tucker, Facilities Safety Officer				
Created By	Derick Pacio, Operations Manager				
	Deflek Lacio, Operations Manager				

## Contact Info For more information about this JSA and other JSAs, contact: UNC-CH Department of Environment, Health and Safety 1120 Estes Drive Extension, Chapel Hill NC 27599 CB# 1650 (919) 962-5507 # https://ehs.unc.edu/